

OILIGHT Connectors

ORDERING INFORMATION

2700

SERIES

12

SEAL RING
RETAINERHOUSING

C

OPTIONS

SERIES

2700
2721
2800
2850

SEAL RING RETAINERS

12 = 12 Gage Wire Insert
14 = 14 Gage Wire Insert
16 = 16 Gage Wire Insert

OPTIONS

26 = Receptacle Cap (2875) to be used with 2721 Series Outlet

MOUNTING OPTIONS



2026




2027

RELATED PRODUCTS




2100



2200



2400



1400 PANEL

DIMENSIONS

2100

5 1/2" W
6 1/2" L
2" D

2721

5 1/2" W
6 1/2" L
4" D



SNELSON OILFIELD LIGHTING
3619 Alice Street
Fort Worth, TX 76110

817-926-0571 Phone
817-926-0741 Fax
www.snelsonlights.com



APPLICATIONS:

- Drilling Rigs
- Offshore Platforms
- Chemical Plants
- Pharmaceutical Plants
- Mining
- Pulp and Paper Mills
- Shipyard Facilities
- Coastal Marine Facilities
- Power Generation Plants
- Hazardous Storage Areas
- Marine Shipping
- Cold Storage Facilities
- Corrosive Atmospheres

FEATURES:

- **2700** Cast Aluminum Splice Box and Cover Plate, Quad Cable Outlets with Polycarbonate Wire Insert / Retainers (specify wire size)
- **2721** Cast Aluminum Splice Box with Polycarbonate Cover, Quad Cable Outlets and Polycarbonate Insert / Retainers (specify wire size)
- **2800** Line Connector Polycarbonate with Keyed Positive Alignment to Accept the 2850 Plug Connector
- **2850** Plug Connector with Keyed Positive Alignment to be Used with 2800 (Line Connector) or the Outlet Series (2100, 2200, 2400 or 2721) Insert and Plug
Constructed of Polycarbonate
- Non Rated

**Spanning the Globe with Quality Lighting
for Over 48 Years**